

PORTABLE DUST EXTRACTION SYSTEM



► THE PORTABLE DUST EXTRACTION SYSTEM

The portable dust extraction system collects the sanding dust in a container and the same can be disposed later. Handling and disposal of the sanding dust becomes easy making the workplace clean and safe

► Technical Specification

Input Supply : 1 Ph, 230 V, 50 HZ

Power absorption : 1.1 kW

Suction capacity : 2.6 m³/min

Tank Capacity : 40 L

Max Vacuum : 2200 mm H₂O

Dimension : 562 x 500 x 810 mm

Unit weight : 22 kg approx.

► Scope Of Supply

Description	Quantity
Portable unit with tool rack	: 1
Sander hose	: 2
Random orbital sander	: 2

► Features

- Portable dry sanding System with Dual sanders
- High suction capacity of 2.6 m³/min
- Automatic on-off Motor
- Dual Sander weight of 700 gm
- Mounted on trolley with basket for hanging tools
- Long Running Filter
- Multiple Sanding at a time

► Advantages

- Portable & easy to carry all over shop floor
- Ensures clean Environment
- Low weighing sander for user convenience
- Low running costs with long running filter
- Allows dual sanders to work parallel

ATS ELGI

Private Industrial Estate, Kurichy,
Coimbatore - 641021, Tamil Nadu, India.

Visit us at : www.ats-elgi.com | Email : enquiry@ats-elgi.com

Toll Free Number : **1800-203-3544**

Follow us on : [in](#) [f](#) [@](#) [v](#) [x](#)

ATS ELGI authorized dealer